



AV600 Powerline Wi-Fi 3-pack Kit

Instant Wi-Fi & Wired
Network Everywhere

TL-WPA4220 TKIT



Extend Network Using
Existing Electrical Wiring



2 Ethernet Ports
per Extender




Plug and Play

Highlights

One-Touch Configuration

Instantly copy the wireless network name (SSID) and password from your router by pressing the Wi-Fi Clone button. Besides, any changes made to the Wi-Fi settings of any powerline adapter will be automatically applied across the entire Powerline network.



Wi-Fi Clone




Auto-Sync Wi-Fi Settings

Highlights


Extend Wi-Fi to Every Room Using Existing Electrical Wiring

The powerline product TL-WPA4220 TKIT transforms your home's existing electrical circuit into a high-speed network, and brings wired and wireless networks to anywhere there is a power outlet.



AV600 Speeds and 300 Meters Range

Using advanced HomePlug AV technology, TL-WPA4220 TKIT provides stable and high-speed data transmissions of up to 600 Mbps* for ranges up to 300 meters. Stream in HD, game online and download large files without interruption thanks to reliable powerline links.



*Listed HomePlug AV speed refers to the theoretical maximum physical-layer data transfer rate. Actual data speeds vary and are limited by the product's Ethernet port and other network conditions such as data traffic, electrical noise, and wiring issues.

Features

Speed

- Wireless N Standard – Wi-Fi speed of up to 300Mbps
- HomePlug AV – Provides up to 600Mbps high-speed data transmission over a home's existing electrical wiring
- Multiple Ethernet Ports – Create faster connections with PCs, consoles, STB and more
- Speed Optimization – Supports IGMP managed multicast IP transmission, optimizing IPTV streaming

Range

- 300 Meters Range – Up to 300 meters/1000 feet range over existing electrical wiring

Ease of Use

- Wi-Fi Clone – Allows powerline extenders to copy the network name (SSID) and password from your router with one simple touch
- Auto-Sync Wi-Fi Settings – Automatically adopts Wi-Fi settings from your existing powerline network
- TP-Link tpPLC – Allows you to easily manage your network using the intuitive tpPLC App or the tpPLC Utility
- Plug and Play – Set up your powerline network in minutes


Security

- Pair Button – Provides a connection with 128-bit AES encryption, at the touch of "Pair" button
- Parental Controls – Manage when and how connected devices can access the internet
- Encryptions for Secure Network – WPA-PSK/WPA2-PSK encryptions provide active protection against security threats

Specifications

Hardware

- Transmission Speeds:
 - Powerline: up to 600 Mbps
 - Ethernet: 10/100 Mbps
- Standards and Protocols:
 - HomePlug AV, IEEE 1901, IEEE 802.3, IEEE 802.3u, IEEE 802.11b/g/n
- Interface:
 - TL-WPA4220: 2 Ethernet Ports
 - TL-PA4010: 1 Ethernet Port
- Plug Type: EU
- Button: Pair, Reset, Wi-Fi Clone
- LED Indicator: Power, Powerline, Ethernet, Wi-Fi
- Dimensions (W x D x H):
 - TL-WPA4220: 2.1 × 1.6 × 3.7 in. (54 × 40 × 94 mm)
 - TL-PA4010: 2.0 × 1.1 × 2.6 in. (52 × 28.5 × 65 mm)
- IGMP: IGMP v1/v2/v3
- Power Consumption:
 - TL-WPA4220: Maximum: 5.6W, Typical: 5.2W
 - TL-PA4010: Maximum: 2.6W, Typical: 2.3W
- Range: Up to 300 meters/1000 feet over existing electrical wiring
- Compatibility:
 - Compatible with all HomePlug AV & AV2 standard powerline adapters



Specifications

Software

- Modulation Technology: OFDM

- Security:

Wireless: WPA-PSK / WPA2-PSK, WEP Encrptions

Powerline: 128-bit AES Encryption

- Management Tools:

tpPLC-Scan the QR code to download TP-Link tpPLC App



Or download new tpPLC Utility on PCs: www.tp-link.com.

Others

- Package Contents

AV600 Powerline Wi-Fi 3-pack Kit

2 × TL-WPA4220 (Wi-Fi Extender)

1 × TL-PA4010

3 × Ethernet Cable

Quick Installation Guide

- Certification

CE, RoHS

- System Requirements

Windows 10/8.1/8/7/Vista/XP, Mac OS, Linux

- System Requirements for tpPLC Utility

Windows 10/8.1/8/7/Vista/XP and Mac OS X (10.7- 10.12)

- Environment

Operating Temperature: 0°C~40°C (32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing



For more information, please visit

<https://www.tp-link.com/en/products/details/TL-WPA4220T-KIT.html>

or scan the QR code on the left.

* Listed AV and Wi-Fi speeds refer to the theoretical maximum physical-layer data transfer rate. Actual data speeds vary and are influenced by the home's Wi-Fi/electrical/physical environment, and if adapters are placed on the same home circuit.

Specifications are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright ©2019 TP-Link Technologies Co., Ltd. All rights reserved.

*Compatible with all HomePlug AV and AV2 Standard Powerline adapters. This product may not be compatible with routers or gateways with firmware that has been altered, is based on open source programs, or are non-standard or outdated.

*Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless data throughput and wireless coverage are not guaranteed and will vary as a result of network conditions, client limitations, and environmental factors, including building materials, obstacles, volume and density of traffic, and client location.

*Maximum Powerline signal rates are the physical rates derived from HomeplugAV/AV2 specifications. Actual Powerline data throughput and Powerline range are not guaranteed and will vary as a result of network conditions and environmental factors, including electrical interference, volume of traffic and network overhead, AFCI circuit breaker, and Powerline being located in a separate circuit.