

Achieve Litespeed



With its kink-resistant tubing and matt-black styling, the MasterLiquid Lite 240 is a Cooler Master original design and attractive entry into liquid cooling. Reliability, performance and quiet operation are ensured by its unique Dual Dissipation Pump and dual 120mm Air Balance fan design. Whether you're building new or just upgrading, it's easy to install on the latest Intel or AMD systems and 240mm radiator fits almost all PC chassis.

*AMD AM4/Intel LGA 2066 brackets are included

Features

Easy and Reliable - An easy install, reliable and low noise all-in-one liquid cooler for Intel and AMD systems

Dual Dissipation Pump - Its unique low-profile dual chamber pump design features a low vibration pump for cool and quiet operation.

Robust FEP Tubing - Robust and extra thick FEP tubing ensures kink-resistance to ensure full liquid flow-rate and eliminates potential evaporation.

Air Balance Fan Design - 120mm Air Balance fan's silent driver IC smoothens fan operation, reducing fan clicks and vibrations.

Fits almost all cases - Fits almost all PC chassis with dual 120mm fans mount near the CPU area.

EAN code	4719512063200
UPC code	884102035883
Net weight	1.138Kg
Gross weight	1.82Kg
Carton dimension (L x W x H)	59 x 34.5 x 31 cm

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	1296	36	n/a
40'	2736	36	n/a
40 HQ	3192	42	n/a

Specifications & Packing Information

Product Name		MasterLiquid Lite 240
Product Number		MLW-D24M-A20PW-R1
CPU Socket		Intel® LGA 2066/ 2011-v3/ 2011/ 1366/ 1151/1150/ 1156/ 1155/ 775 socket AMD AM4 /AM3+/ AM3/ AM2+/AM2/ FM2+/ FM2/ FM1 socket
Main System	Dimensions	62 x 62 x 36.4 mm (2.4 x 2.4 x 1.4")
	Power Connector	4-Pin
Waterblock	Dimensions	80.3 x 76 x 42.2mm (3.2 x 3.0 x 1.7")
Pump	MTTF	70,000 hours
	Noise Level	< 15 dBA
	Connector	3-Pin
	Rated Voltage	12 VDC
	Load Current	0.3 A
	Power Consumption	3.96 W
Radiator	Dimension	277 x 119.6 x 27mm (10.9 x 4.7 x 1.1")
	Material	Aluminum
Fan	Dimensions	120 x 120 x 25 mm (4.7 x 4.7 x 1")
	Speed	650 ~ 2000 RPM (PWM) ± 10%
	Air Flow	66.7 CFM ± 10%
	Air Pressure	2.34 mmH ₂ O ± 10%
	MTTF	160,000 hours
	Noise Level	6 ~ 30 dBA
	Connector	4-Pin (PWM)
	Rated Voltage	12 VDC